



Artikelnummer RST Article Code RST	Hersteller- nummer Manufacturer Code RST	Größe Size	Gewinde Entry Thread	KB Kabelmantel aussen/Clamping R. Outer Sheath (mm)		KB Kabelmantel innen/Clamping R. Inner Sheath (mm)		KB Armierung / Clamping Range Armour (mm)		 1/2	L (mm)	H max. (mm)	VPE* PU*
				≥	≤	≥	≤	≥	≤				
00849009V1	ADE4N1503SSN	11	NPT 1 1/2"	35.0	48.0	29.0	41.0	0.2	2.5	64/64	28.5	97.0	1

Material	Edelstahl 1.4404
Druckring	Messing, vernickelt
Dichteinsatz	Silikon
Armierungsring	Edelstahl 1.4404
Armierungskonus	Edelstahl 1.4404
Einsatztemperatur	-60°C bis +140°C
Schutzart gem. IEC 60529	IP66/IP68 (Montageanleitung berücksichtigen)
ATEX-Kennzeichnung	Ex II 2 GD / Ex db IIC / Ex eb IIC / Ex tb IIIC Ex I M2 / Ex db I / Ex eb I
Zugentlastung gem. EN 60079-0 (Anhang A)	25 %
Empfohlenes Anzugsdrehmoment	Hutmutter 135.0 Nm Stutzen 100.0 Nm
CE-Kennzeichnung	ja (Richtlinie 2014/34/EU)
Zolltarif-Nummer	85369010
Gewicht	0.720 kg
EAN-Nummer	3589350035896
RoHS (2015/863/EU)	konf. (Inanspruchnahme Ausnahme 6c)
REACH/SVHC (Art. 33 1907/2006)	Blei enthalten
Konfliktminerale (Dodd-Frank Act)	keine Konfliktminerale enthalten

Für besondere Bedingungen oder Einschränkungen siehe entsprechende Produktdokumentation.

Material	Stainless Steel 316L
Pressure Ring	Nickel Plated Brass
Sealing	Silicone
Reinforcement Ring	Stainless Steel 316L
Reinforcement Cone	Stainless Steel 316L
Operating Temperature	-60°C to +140°C
Protection Class rel. IEC 60529	IP66/IP68 (Consider mounting instruction)
ATEX Marking	Ex II 2 GD / Ex db IIC / Ex eb IIC / Ex tb IIIC Ex I M2 / Ex db I / Ex eb I
Strain relief rel. EN 60079-0 (Appendix A)	25 %
Recommended Tightening Torque	Cap 135.0 Nm Body 100.0 Nm
CE Marking	yes (Directive 2014/34/EU)
Customs Tariff Number	85369010
Weight	0.720 kg
EAN Code	3589350035896
RoHS (2015/863/EU)	compliant (claim exception 6c)
REACH/SVHC (Art. 33 1907/2006)	contain lead
Konfliktminerale (Dodd-Frank Act)	contain no conflict minerals

For specific conditions or limitations please see relevant product documentation.



Kabelverschraubungen Ex Ex Cable Glands ADE4F / NPT

Produktdokumentation Product Documentation



* Mindestbestellmenge (MOQ) kann größer sein als Verpackungseinheit (VPE).

* Minimum order quantity (MOQ) can be larger than packaging unit (PU).

RST Rabe-System-Technik und Vertriebs-GmbH
Otto-Lilienthal-Strasse 19
49134 Wallenhorst

DEUTSCHLAND

+49 5407 8766-0

+49 5407 8766-99

info@rst.eu

www.rst.eu