

CERTIFICATE OF COMPLIANCE

Certificate Number 20170315-E199260
Report Reference E199260-20170314
Issue Date 2017-MARCH-15

Issued to: BIMED TEKNIK ALETLER SAN TIC A S
BEYLIKDUZU MEVKII
SS BAKIR VE PIRINC SAN
ORKIDE CD NO 15
34524 ISTANBUL TURKEY

This is to certify that POWER AND CONTROL TRAY CABLE CONNECTORS
representative samples of See Addendum Page for Models


Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL50E, Enclosures for Electrical Equipment, Environmental
Considerations

Additional Information: UL 514B, Conduit, Tubing and Cable Fittings
See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE


Certificate Number 20170315-E199260
Report Reference E199260-20170314
Issue Date 2017-MARCH-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Cable Fittings, Series Orion, KBA followed by numerals 1 thru 10, may be followed by S, XS, XM ,LT or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS. Thread sizes 1/2 to 5 in. NPT inclusive or M20 to M130 inclusive.

Cable Fittings, Series Orion Universal, KBAU followed by numerals 1 thru 10, may be followed by S, XS, XM , LT or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS. Thread sizes 1/2 to 5 in. NPT inclusive or M20 to M130 inclusive.

Cable Fittings, Series Orion Universal, KBAO followed by numerals 1 thru 10, may be followed by S, XS, XM LT or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS. Thread sizes 1/2 to 5 in. NPT inclusive or M20 to M130 inclusive.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

