

CERTIFICATE OF COMPLIANCE

Certificate Number E493186
Report Reference E493186-20201104
Date 2020-November-05

Issued to: BIMED TEKNIK ALETLER SAN TIC A S
BEYLIKDUZU MEVKII
SS BAKIR VE PIRINC SAN
ORKIDE CD NO 15
ISTANBUL34524 TR

**This is to certify that
representative samples of**

CONDUIT FITTINGS FOR USE IN ZONE CLASSIFIED
HAZARDOUS LOCATIONS

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.


Standard(s) for Safety: See Addendum Page for Standards

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E493186
Report Reference E493186-20201104
Date 2020-November-05

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

USL - Ventilation Plugs for use in Hazardous Locations, thread sizes M12, Series BBVP, Cat. No. S, M, H or UH, followed by BBVP, followed by X, followed by -01 or -01L, followed by blank, followed by blank or L, followed by TL6 for use in Class I, Zone 1, AEx eb IIC Gb.

Ventilation Plugs for use in Hazardous Locations, thread sizes M12, Series BBVP, Cat. No. S, M, H or UH, followed by BBVP, followed by X, followed by -01 or -01L, followed by blank, followed by blank or L, followed by blank for use in Class I, Zone 1, AEx eb IIC Gb; Zone 21, AEx tb IIIC Db

CNL - Ventilation Plugs for use in Hazardous Locations, thread sizes M12, Series BBVP, Cat. No. S, M, H or UH, followed by BBVP, followed by X, followed by -01 or -01L, followed by blank, followed by blank or L, followed by TL6 for use in Class I, Zone 1, Ex eb IIC Gb.

Ventilation Plugs for use in Hazardous Locations, thread sizes M12, Series BBVP, Cat. No., S, M, H or UH, followed by BBVP, followed by X, followed by -01 or -01L, followed by blank, followed by blank or L, followed by blank for use in Class I, Zone 1, Ex eb IIC Gb; Zone 21, Ex tb IIIC Db.

M12 INOX TL6 M12 INOX TL10
SBBVP-X01 SBBVP-X01L
MBBVP-X01 MBBVP-X01L
HBBVP-X01 HBBVP-X01L
UHBBVP-X01 UHBBVP-X01L

Standard No. UL 60079-0 Electrical Apparatus for Explosive Gas Atmospheres – Part 0: General Requirements

Standard No. UL 60079-7, Explosive Atmospheres – Part 7: Equipment protection by increased safety "e"

Standard No. UL 60079-31, Explosive Atmospheres – Part 31: Equipment Dust Ignition Protection by Enclosure "t"

Standard No. CSA C22.2 No. 60079-0, Electrical Apparatus for Explosive Gas Atmospheres - Part 0: General Requirements,

Standard No. CSA C22.2 No. 60079-7, Explosive Atmospheres - Part 7: Equipment Protection by Increased Safety "e"

Standard No. CSA C22.2 No. 60079-31, Explosive Atmospheres - Part 31: Equipment Dust Ignition Protection by Enclosure "t"



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>