

Material	Messing, vernickelt Edelstahl
Dichteinsatz	Neopren
O-Ring	Perbunan
Einsatztemperatur	-20°C bis +80°C
Gewinde	Metrisch nach ISO 965-1 / 965-3
Schutzart	IP66 / IP68
ATEX-Kennzeichnung	Ex II 2 GD Ex eb IIC / Ex nRc IIC / Ex tb IIIC

Material	Nickel Plated Brass Stainless Steel
Sealing	Neoprene
O-Ring	Perbunan
Operating Temperature	-20°C to +80°C
Thread	Metric acc. to ISO 965-1 / 965-3
Protection Class	IP66 / IP68
ATEX Marking	Ex II 2 GD Ex eb IIC / Ex nRc IIC / Ex tb IIIC

Für besondere Bedingungen oder Einschränkungen siehe entsprechende Produktdokumentation.

For specific conditions or limitations please see relevant product documentation.

Zulassungen / Approvals **ATEX** IECEx
 INERIS13ATEX0008X IECExINE13.0003X

Artikel-Nummer RST Article Code RST	Hersteller- Nummer Manufacturer Code	Hersteller Manufacturer	Größe Size	Gewinde Entry Thread	Klemmbereich Clamping Range (mm)		Schirmungsstärke Braid Thickness (mm)		L (mm)	H (mm)	VPE PU
					≥	≤					
NP/brass											
00192124V1	CAP192124V1	CAPRI	4	M12x1.5	4.0	6.5	0.70	15/15	6.5	18.0	lose/ loose
00192154V1	CAP192154V1		4	M16x1.5	4.0	6.5	0.70	15/18	6.5	18.0	lose/ loose
00192164V1	CAP192164V1		5	M16x1.5	5.5	10.0	0.70	20/20	6.5	24.0	lose/ loose
00192194V1	CAP192194V1		5	M20x1.5	5.5	10.0	0.70	20/22	6.5	24.0	lose/ loose
00192204V1	CAP192204V1		6	M20x1.5	7.5	13.0	0.80	24/24	6.5	27.0	lose/ loose
00192244V1	CAP192244V1		6	M25x1.5	7.5	13.0	0.80	24/27	7.0	27.0	lose/ loose
00192254V1	CAP192254V1		7	M25x1.5	11.5	18.0	0.85	30/30	7.0	28.0	lose/ loose
00192314V1	CAP192314V1		7	M32x1.5	11.5	18.0	0.85	30/34	8.0	28.0	lose/ loose
00192324V1	CAP192324V1		8	M32x1.5	17.5	24.5	0.95	38/38	8.0	30.0	lose/ loose
00192394V1	CAP192394V1		8	M40x1.5	17.5	24.5	0.95	38/43	8.0	30.0	lose/ loose
00192404V1	CAP192404V1		9	M40x1.5	24.0	32.0	1.00	47/47	8.0	33.0	lose/ loose
00192494V1	CAP192494V1		9	M50x1.5	24.0	32.0	1.00	47/54	9.0	33.0	lose/ loose
00192504V1	CAP192504V1		10	M50x1.5	31.0	40.5	1.15	57/57	9.0	37.0	lose/ loose
00192624V1	CAP192624V1		10	M63x1.5	31.0	40.5	1.15	57/68	10.0	37.0	lose/ loose
00192634V1	CAP192634V1		11	M63x1.5	39.0	53.0	1.75	75/75	10.0	48.0	lose/ loose
1.4404/316L											
00192129V1	CAP192129V1	CAPRI	4	M12x1.5	4.0	6.5	0.70	15/15	15.0	18.0	lose/ loose
00192159V1	CAP192159V1		4	M16x1.5	4.0	6.5	0.70	15/18	15.0	18.0	lose/ loose
00192169V1	CAP192169V1		5	M16x1.5	5.5	10.0	0.70	20/20	15.0	24.0	lose/ loose
00192199V1	CAP192199V1		5	M20x1.5	5.5	10.0	0.70	20/22	15.0	24.0	lose/ loose
00192209V1	CAP192209V1		6	M20x1.5	7.5	13.0	0.80	24/24	15.0	27.0	lose/ loose
00192249V1	CAP192249V1		6	M25x1.5	7.5	13.0	0.80	24/27	15.0	27.0	lose/ loose
00192259V1	CAP192259V1		7	M25x1.5	11.5	18.0	0.85	30/30	15.0	28.0	lose/ loose
00192319V1	CAP192319V1		7	M32x1.5	11.5	18.0	0.85	30/34	15.0	28.0	lose/ loose
00192329V1	CAP192329V1		8	M32x1.5	17.5	24.5	0.95	38/38	15.0	30.0	lose/ loose
00192399V1	CAP192399V1		8	M40x1.5	17.5	24.5	0.95	38/43	15.0	30.0	lose/ loose
00192409V1	CAP192409V1		9	M40x1.5	24.0	32.0	1.00	47/47	15.0	33.0	lose/ loose
00192499V1	CAP192499V1		9	M50x1.5	24.0	32.0	1.00	47/54	15.0	33.0	lose/ loose
00192509V1	CAP192509V1		10	M50x1.5	31.0	40.5	1.15	57/57	15.0	37.0	lose/ loose
00192629V1	CAP192629V1		10	M63x1.5	31.0	40.5	1.15	57/68	15.0	37.0	lose/ loose
00192639V1	CAP192639V1		11	M63x1.5	39.0	53.0	1.75	75/75	15.0	48.0	lose/ loose

Weitere Produkte des Herstellers auf Anfrage. / Further products of the manufacturer on request.

